

## BPET-CC

PET编织管  
Braided hose

+150°C / -55°C    +302°F / -67°F

Material: Polyester



- 防摩擦性能及耐化学品性能好
- 表面有施加特殊涂层, 使此编织管的冷切变得可能, 使用普通的剪刀裁切编织管也不会散开
- 适用于空间有限的场合用来保护和捆扎线缆线束
- very good protection against chafing good and resistance against chemical solvents
- braided hose that is specially coated for cold-cut capabilities, therefore it can be cut with normal scissors without intention for frizzling
- bundling and protection of cables and wires also at limited application spaces

温度范围 / Temperature range  
弯曲性能 / 柔韧性 / Flexibility/Ductility  
动态性能 / Dynamic  
机械防护性能 / Mechanical protection  
防火性能 / Fire precaution performance  
耐化学品性能 / Chemical resistance  
耐候性 / Resistance to weathering

min.					max.



产品号 Part No. <sup>1)</sup>	名义尺寸 Nominal width	应用范围 Application range		包装单元 PU
		D <sub>min.</sub> in mm	D <sub>max.</sub> in mm	
黑色 / black	NW			m
BPET-CC04B.50	04	3	10	50
BPET-CC06B.50	06	4	10	50
BPET-CC08B.50	08	6	11	50
BPET-CC10B.50	10	8	14	50
BPET-CC12B.50	12	10	16	50
BPET-CC14B.50	14	12	20	50
BPET-CC16B.50	16	14	22	50
BPET-CC20B.50	20	18	25	50
BPET-CC25B.25	25	18	33	25
BPET-CC30B.25	30	30	44	25
BPET-CC35B.20	35	30	40	20
BPET-CC40B.20	40	28	42	20
BPET-CC45B.20	45	38	60	20
BPET-CC50B.20	50	45	60	20

按要求盘绕 / Bulk coils on request.

您可以通过以下地址查询更多的技术信息 / You can find more technical information here

CADENAS – 产品CAD数据目录 / eCATALOG solutions electronic CAD catalog: <https://fraenkische-ip.partcommunity.com>

<sup>1)</sup> FIPJACK® 编织管编码规则 / Part numbering key for FIPJACK® protection sleeves: [www.fraenkische.com/fipjack-part-no](http://www.fraenkische.com/fipjack-part-no)



# BPET-CC 产品性能 / Product performances

应用性能 <i>Application performances</i>	特性 <i>Characteristics</i>	单位 <i>Unit</i>	规范标准 <i>Standards, specifications</i>	备注 <i>Remark</i>
温度范围 / <i>Temperature range</i>	-55 到 / <i>to</i> +150 -67 到 / <i>to</i> +302	°C °F	IS FIP	

防火性能 / <i>Fire safety performances</i>				
不含卤素和镉 / <i>Free from halogens and cadmium</i>	是 / <i>yes</i>			
防火特性 / <i>Flammability</i>	自熄 <i>self-extinguishing</i>		FMVSS 302	

测试条件参照EN ISO 139 , 温度 23°C / 湿度50% r. F. (如未注明测试条件). IS FIP = FIP内部测试规范  
*Tests carried out acc. EN ISO 139 at 23°C / 50% r. h. (if not indicated differently). IS FIP = Internal Specification FIP*

Die hier enthaltenen Angaben – einschließlich der Abbildungen und graphischen Darstellungen – entsprechen dem aktuellen Stand unserer Kenntnisse und sind nach bestem Wissen richtig und zuverlässig. Sie stellen jedoch keine verbindliche Eigenschaftszusicherung dar. Der Anwender der aufgeführten Produkte hat in eigener Verantwortung über deren Eignung für den vorgesehenen Einsatz zu entscheiden. Unsere Haftung für dieses Erzeugnis richtet sich ausschließlich nach unseren Liefer- und Zahlungsbedingungen. Spezifikationen können von FRÄNKISCHE Industrial Pipes (FIP) ohne Vorankündigung geändert werden. Zudem behält sich FIP das Recht vor, ohne Mitteilung an den Käufer an Werkstoffen oder deren Verarbeitungen Änderungen vorzunehmen, die die Einhaltung zutreffender Spezifikationen nicht beeinträchtigen oder sogar verbessern.

*The provided data, images and technical specification drawings reflect the current engineering level and are to the best of our knowledge. This does not include any liability regarding the final application. Users of the products have to make their own evaluation to determine the suitability for a specific application. Our liability for these products considers the stated level within our General Conditions only. FRAENKISCHE Industrial Pipes (FIP) reserves the right to adjust specified data and values as well as implementing technical adjustments of the products e. g. change of materials and processing technologies without prior notice as long as the specified values are not reduced.*

FRÄNKISCHE Industrial Pipes GmbH & Co. KG / Hellinger Str. 1 / 97486 Königsberg/Germany  
Phone +49 9525 88-0 / Fax +49 9525 88-155 / info@fraenkische-ip.com / www.fipsystems.com

CN/E.3251/1.02.19 FIP / 如有更改, 恕不另行通知 / *Subject to change without notice*

01.05.2024, V5.0