

JSPA

直型管接头 Fitting

+120°C +248°F
-50°C -58°F

Material: PA6 MOD V0 SGA



- 直接头, 适配 FIPLOCK® 标准波纹管NW56以上粗波形
- 自熄, 耐大多数常见化学品
- 耐UV性能优异
- 小袋包装, 预装发货


- straight fitting suitable for FIPLOCK® corrugated conduits with coarse profile starting from nominal width 56
- self-extinguishing and resistant against most chemical media commonly used
- excellent UV-resistance
- pre-assembled in small packing units

温度范围 / Temperature range
UV-防护 / UV protection
低温性能 / Cold environment performance
机械强度 / Mechanical strength

min.				max.			



产品号 Part No. ¹⁾	名义尺寸 Nominal width	波型 Profile ²⁾	尺寸 Dimensions in mm					重量 Weight	包装单元 PU
			ØD	L	E	F	G		
黑色 / black	NW	C	ØD	L	E	F	G	g	个 / Pcs
JSPA-56M6PB	56	C	102,0	52,3	66,0	60,0	-	129,1	2
JSPA-70M6PB	70	C	120,0	52,3	80,0	60,0	100,0	148,8	2
JSPA-95M6PB	95	C	146,0	52,3	108,0	74,0	131,0	190,6	2
JSPA-125M6PB	125	C	192,4	79,6	147,0	95,0	176,0	357,6	1



您可以通过以下地址查询更多的技术信息 / You can find more technical information here

CADENAS – 产品CAD数据目录 / eCATALOGsolutions electronic CAD catalog: <https://fraenkische-ip.partcommunity.com>

¹⁾ FIPLOCK® XL 管接头编码规则 / Part numbering key for FIPLOCK® XL fittings: www.fraenkische.com/fiplock-xl-part-no

²⁾ 波纹管波型 / Conduit profiles: www.fraenkische.com/fipsystems-profiles

³⁾ FIPLOCK® XL JSPA/JWPA 组装说明 / Assembly instruction for FIPLOCK® JSPA/JWPA: www.fraenkische.com/assembly-fiplock-xl-jspa-jwpa



应用性能 <i>Application performances</i>	特性 <i>Characteristics</i>	单位 <i>Unit</i>	规范标准 <i>Standards, specifications</i>	备注 <i>Remark</i>
温度范围 / <i>Temperature range</i>	-50 到 / <i>to</i> +120 -58 到 / <i>to</i> +248	°C °F	IS FIP	
温度 (短周期) / <i>Temperature (short-term)</i>	150 (500 h); 160 (100 h) 302 (500 h); 320 (100 h)	°C °F	IS FIP	

系统密封性能 / <i>System tightness</i>				
IP 等级 / <i>IP rating</i>	IP66/IP67/IP68/IP69 (IP69K)		IEC EN 60529	

防火性能 / <i>Fire safety performances</i>				
不含卤素和镉 / <i>Free from halogens and cadmium</i>	是 / <i>yes</i>			
阻燃等级 / <i>Fire classification</i>	V0		UL 94	
氧指数 / <i>Oxygen index</i>	>32	%	EN ISO 4589-2	
灼热丝测试 / <i>Glow wire test</i>	960 / 1760	°C / °F	IEC 60695	
火灾危害等级 / <i>Fire hazardous level</i>	HL2 R22 / HL3 R23		EN45545-2	
火焰蔓延指数 / <i>Flame spread index</i>	符合 / <i>compliant</i>		ASTM E162	参照 NFPA 130 / <i>acc. NFPA 130</i>
烟雾密度 / <i>Smoke density</i>	符合 / <i>compliant</i>		ASTM E662	参照 NFPA 130 / <i>acc. NFPA 130</i>
烟雾毒性 / <i>Smoke toxicity</i>	符合 / <i>compliant</i>		BSS 7239 / SMP 800-C	
热释放量 (焓) / <i>Heat release (Enthalpy)</i>	19,4 (8265)	MJ/kg (BTU/lb)	ASTM E1354	50 kW/m ² 热通量 50 kW/m ² heat flux

耐候性 / <i>Weathering performances</i>				
UV- 及耐候性能 <i>UV and weathering performance</i>	优异 <i>excellent</i>		IS FIP	可达 40 年 <i>up to 40 years</i>

测试条件参照EN ISO 139 , 温度 23°C / 湿度50% r. h. (如未注明测试条件). IS FIP = FIP内部测试规范
Tests carried out acc. EN ISO 139 at 23°C / 50% r. h. (if not indicated differently). IS FIP = Internal Specification FIP

我们尽我们的知识水平所提供的数据, 图片和技术规格图档反映了当前的工程技术水平. 这并不包含对最后应用有关的任何责任. 产品用户需根据应用要求自行进行评估. 以确定产品是否符合特殊应用条件. 我们对产品的责任只考虑一般规定条件下的水平. FIP保留对产品数据和数值进行技术调整的权利. 例如更改材料和加工工艺, 在保证产品性能数值不下降的情况下不会另行通知.

The provided data, images and technical specification drawings reflect the current engineering level and are to the best of our knowledge. This does not include any liability regarding the final application. Users of the products have to make their own evaluation to determine the suitability for a specific application. Our liability for these products considers the stated level within our General Conditions only. FRAENKISCHE Industrial Pipes (FIP) reserves the right to adjust specified data and values as well as implementing technical adjustments of the products e. g. change of materials and processing technologies without prior notice as long as the specified values are not reduced.