

TDPA

穿线器

Draw-in-tool

+150°C +302°F
-40°C -40°F

Material: PA66




- 用于辅助将线缆束装入开口的FIPLOCK® 标准波纹管中的穿线器
- 有孔型和手柄型可选
- draw-in tool for cables and conductors into slit FIPLOCK® corrugated conduits
- available as variant with hole or grip



产品号 Part No. ¹⁾	名义尺寸 Nominal width	类型 Model	包装单元 PU
黑色 / black	NW		个 / Pcs
TDPA-04B-01	4,5 – 07	孔型 / with hole	10
TDPA-04B-02	4,5 – 07	手柄型 / with grip	10
TDPA-07B-01	07 – 29	孔型 / with hole	10
TDPA-07B-02	07 – 29	手柄型 / with grip	10



孔型 / with hole



手柄型 / with grip

CADENAS – 产品CAD数据目录 / eCATALOGsolutions electronic CAD catalog: <https://fraenkische-ip.partcommunity.com>

¹⁾ FIPLOCK® 附件编码规则 / Part numbering key for FIPLOCK® accessories: www.fraenkische-ip.com/fiplock-accsy-part-no

关于产品库存, 交期, 尺寸及颜色等问题请联系我们本地的经销商或客服。

Please contact our local distribution partner or our customer service regarding product availability, lead time, other sizes and colours.

我们尽我们的知识水平所提供的数据, 图片和技术规格图档反映了当前的工程技术水平。这不包含对最后应用有关的任何责任。产品用户需根据应用要求自行进行评估。以确定产品是否符合特殊应用条件。我们对产品的责任只考虑一般规定条件下的水平。FIP保留对产品数据和数值进行技术调整的权利。例如更改材料和加工工艺, 在保证产品性能数值不下降的情况下不会另行通知。

The provided data, images and technical specification drawings reflect the current engineering level and are to the best of our knowledge. This does not include any liability regarding the final application. Users of the products have to make their own evaluation to determine the suitability for a specific application. Our liability for these products considers the stated level within our General Conditions only. FRAENKISCHE Industrial Pipes (FIP) reserves the right to adjust specified data and values as well as implementing technical adjustments of the products e. g. change of materials and processing technologies without prior notice as long as the specified values are not reduced.