

ME-2-TR-M


柔性公制弯头 Fitting

+105°C +221°F
-40°C -40°F


材料: 镀镍黄铜 / Material: Brass nickel plated
管子材料 AISI 304不锈钢 / conduit stainless steel AISI 304



- 带公制螺纹弯接头
 - 根据管子类型, 最高IP等级可达IP68
 - FIPMETAL[®] 弯头灵活, 可自由便捷的设置管子的朝向
 - 尽管具有灵活性, 但金属波纹管具有一定的刚度, 所以在安装后朝向相对固定
- curved elbow fitting with metric threads
 - provides up to IP68 tightness, depending on the type of pipe
 - flexible range of the FIPMETAL[®] elbow connector enables freely selectable outlet directions of the pipes
 - despite the flexibility, the inherent rigidity of the bendable angle range is maintained and the exit direction is therefore fixed



产品号 Part No. ¹⁾		螺纹类型 Thread type	适配管子尺寸NW Fits to conduit NW	尺寸 (mm) Dimensions in mm (nom.)			包装单元 PU
FIP	EURO 2000	公制 / metric	NW	D	C	L	个 / Pcs
ME-210-53141-TR	53141-Tr,210	M16x1,5	10,0	22,0	20,0	9	20
ME-212-53142-TR	53142-Tr,212	M16x1,5	12,0	26,0	24,0	9	20
ME-212-53143-TR	53143-Tr,212	M20x1,5	12,0	26,0	24,0	9	20
ME-216-53144-TR	53144-Tr,216	M20x1,5	15,5	29,0	27,0	9	10
ME-221-53145-TR	53145-Tr,221	M25x1,5	20,5	35,0	33,0	9	5
ME-227-53146-TR	53146-Tr,227	M32x1,5	26,5	45,0	43,0	11	1
ME-235-53147-TR	53147-Tr,235	M40x1,5	34,5	54,0	52,0	11	1
ME-240-53148-TR	53148-Tr,240	M50x1,5	39,5	62,0	60,0	14	1
ME-250-53149-TR	53149-Tr,250	M63x1,5	50,5	77,0	74,0	14	1



您可以通过以下地址查询更多的技术信息 / You can find more technical information here

CADENAS - 产品CAD数据目录 / eCATALOGsolutions electronic CAD catalog: <https://fraenkische-ip.partcommunity.com>

¹⁾ FIPMETAL[®] 产品的编码规则 / Part numbering key for FIPMETAL[®] products: www.fraenkische-ip.com/fipmetal-part-no

²⁾ FIPMETAL[®] 压环类型概览 / Overview FIPMETAL[®] ring types: www.fraenkische-ip.com/fipmetal-ring-types

ME-2-TR-M 产品性能 / Product performances

应用性能 Application performances	特性 Characteristics	单位 Unit	规范标准 Standards, specifications	备注 Remark
温度范围 / Temperature range	-40 到 / to +105 -40 到 / to +221	°C °F	IEC EN 61386	
温度 (短周期) / Temperature (short-term)	140 284	°C °F	IS	
机械性能 / Mechanical performances				
IP 防护性能 / IP Protection range	可达 IP66, IP67, IP68 up to IP66, IP67, IP68		EN 60529	
拔脱强度 / Pull-out strength	高 / high		IS	
抗震动强度 / Vibration strenght	非常好 / very good		IS	
防火性能 / Fire safety performances				
产品防火特性 Fire characteristic of the product	不易燃 not flammable			
耐候性 / Weathering performances				
抗腐蚀性 Resistant to corrosion	符合 compliant		ISO 9227 / DIN 50017SK	

测试条件参照EN ISO 139温度23°C, 湿度 / 50% (如未注明测试条件)。IS FIP = FIP内部测试规范
 Tests carried out acc. EN ISO 139 at 23°C / 50% r. h. (if not indicated different). IS FIP = Internal Specification FIP

安装说明 / Assembling instruction:

螺母 / Nut



金属环 / Ferrule



管密封圈 / Conduit seal



环 / Ring²

本体 / Body

公制柔性弯接头
Flexible curved elbow, metric

我们尽我们的知识水平所提供的数据, 图像和技术规格图反映了当前的工程技术水平。这不对最后应用有关的任何责任。产品用户需根据应用进行自己的评估, 以确定产品是否符合特殊的应用条件。我们对产品的责任只考虑一般规定条件下的水平。FIP保留对产品数据和数值进行技术调整的权力。例如更改材料和加工工艺, 在保证产品性能数值不下降的情况下不会另行通知。

The provided data, images and technical specification drawings reflect the current engineering level and are to the best of our knowledge. This does not include any liability regarding the final application. Users of the products have to make their own evaluation to determine the suitability for a specific application. Our liability for these products considers the stated level within our General Conditions only. FRAENKISCHE Industrial Pipes (FIP) reserves the right to adjust specified data and values as well as implementing technical adjustments of the products e. g. change of materials and processing technologies without prior notice as long as the specified values are not reduced.