

2CPA

可开式波纹管连接器 Conduit connector

+120°C +248°F
-45°C -49°F

Material: PA6 MOD BS SGA



- 可开式波纹管接头, 适配 FIPSPLIT® 可分型波纹管
- 用于连接或延申可分型波纹管
- 特别适用于线缆改造的应用场合
- *divisible conduit fitting (splice) for FIPSPLIT® corrugated conduits*
- *to connect and extend divisible corrugated conduits*
- *suitable for retrofit applications*




IP-防护等级 IP-Protection class

IP44

- 防溅水
Protected against splashing water
- 防止1 mm以上物质进入
Protected against solid objects over 1 mm



产品号 Part No. ¹⁾	名义尺寸 Nominal width	尺寸 Dimensions in mm (nom.)			包装单元 PU
黑色 / black	NW	A	B	C	个 / Pcs
2CPA-45B	45	130,9	64,0	69,0	10
2CPA-70B	70	182,6	90,0	69,0	10
2CPA-100B	100	228,0	112,5	69,0	10



您可以通过以下地址查询更多的技术信息 / You can find more technical information here

CADENAS – 产品CAD数据目录 / eCATALOG solutions electronic CAD catalog: <https://fraenkische-ip.partcommunity.com>

¹⁾ FIPSPLIT® 附件编码规则 / Part numbering key for FIPSPLIT® accessories: www.fraenkische.com/fipsplit-accsy-part-no



2CPA 产品性能 / Product performances

应用性能 <i>Application performances</i>	特性 <i>Characteristics</i>	单位 <i>Unit</i>	规范标准 <i>Standards, specifications</i>	备注 <i>Remark</i>
温度范围 / <i>Temperature range</i>	-45 到 / <i>to</i> +120 -49 到 / <i>to</i> +248	°C °F	IS FIP	
温度 (短周期) / <i>Temperature (short-term)</i>	+ 140 + 284	°C °F	IS FIP	
防火性能 / <i>Fire safety performances</i>				
不含卤素和镉 <i>Free from halogens and cadmium</i>	是 / <i>yes</i>			
阻燃等级 / <i>Fire classification</i>	V2		UL 94	
氧指数 / <i>Oxygen index</i>	>28	%	EN ISO 4589-2	
系统密封性能 / <i>System performances</i>				
IP-等级 / <i>Ingress protection (IP)</i>	IP44		EN60529	

测试条件参照EN ISO 139 , 温度 23°C / 湿度50% r. h. (如未注明测试条件). IS FIP = FIP内部测试规范
Tests carried out acc. EN ISO 139 at 23°C / 50% r. h. (if not indicated differently). IS FIP = Internal Specification FIP

我们尽我们的知识水平所提供的数据, 图片和技术规格图档反映了当前的工程技术水平。这不会对最后应用有关的任何责任。产品用户需根据应用要求自行进行评估。以确定产品是否符合特殊应用条件。我们对产品的责任只考虑一般规定条件下的水平。FIP保留对产品数据和数值进行技术调整的权利。例如更改材料和加工工艺, 在保证产品性能数值不下降的情况下不会另行通知。

The provided data, images and technical specification drawings reflect the current engineering level and are to the best of our knowledge. This does not include any liability regarding the final application. Users of the products have to make their own evaluation to determine the suitability for a specific application. Our liability for these products considers the stated level within our General Conditions only. FRAENKISCHE Industrial Pipes (FIP) reserves the right to adjust specified data and values as well as implementing technical adjustments of the products e. g. change of materials and processing technologies without prior notice as long as the specified values are not reduced.